

Printing date 15.09.2020

Revision: 15.09.2020

## 1 Identification

**Product Name:** POWER STATION

**Other Means of Identification:** Mixture

**Recommended Use of the Chemical and Restriction on Use:** Battery

**Details of Manufacturer or Importer:**

Adventure Operations  
 3/20 Enterprise Drive,  
 Bundoora VIC 3083

**Phone Number:** 1300 657 022

**Emergency telephone number:** 1300 657 022

## 2 Hazard(s) Identification

### Hazardous Nature:

Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

STOT RE 2 H373 May cause damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Sensitisation 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

### Signal Word Warning

### Hazard Statements

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H373 May cause damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

### Precautionary Statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)

# Safety Data Sheet

## according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 1)

P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P321 Specific treatment (see on this label).  
 P314 Get medical advice/attention if you feel unwell.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P391 Collect spillage.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national regulations.

### 3 Composition and Information on Ingredients

#### Chemical Characterization: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

| Hazardous Components: |  |          |
|-----------------------|--|----------|
| CAS: 7782-42-5        | Graphite   | 10 - 30% |
| CAS: 7440-50-8        | Copper   | 7 - 13%  |
|                       | ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410                         |          |
| CAS: 7429-90-5        | Aluminium  | 5 - 10%  |
| CAS: 7440-02-0        | Nickel   | 1 - 5%   |
|                       | ⚠ Carcinogenicity 2, H351; STOT RE 1, H372; ⚠ Skin Sensitisation 1, H317 |          |

#### Additional information:

The battery is sealed hermetically and designed to withstand temperatures and pressures encountered during normal use. Thus, the ingredients have no hazard potential except if the battery is violated or dismantled. If exposed to a fire, mechanical shocks, and electric stress by miss-use, the battery cell case will be breached and the hazardous materials may be released and acrid gas may be emitted. Therefore the batteries should not be short circuited, overcharged, punctured, incinerated, immersed in water, force discharged or exposed to temperatures above the temperature range of the cell or battery.

### 4 First Aid Measures

#### Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.  
 This information is relevant only if the battery is broken and contents are exposed.

#### Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap for at least 15 minutes. Seek medical attention if symptoms occur.  
 This information is relevant only if the battery is broken and contents are exposed.

#### Eye Contact:

In case of eye contact, rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.  
 This information is relevant only if the battery is broken and contents are exposed.

#### Ingestion:

If swallowed, do not induce vomiting. Do not give anything by mouth to an unconscious person. Seek immediate medical attention.  
 This information is relevant only if the battery is broken and contents are exposed.

#### Symptoms Caused by Exposure:

Inhalation: Contents of an open battery may cause respiratory irritation.  
 Skin Contact: Contents of an open battery may cause skin irritation. May cause an allergic skin reaction.  
 Eye Contact: Contents of an open battery may cause eye irritation.  
 Ingestion: The contents of an open battery may cause gastrointestinal irritation.

(Contd. on page 3)

# Safety Data Sheet

## according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 2)

### 5 Fire Fighting Measures

**Suitable Extinguishing Media:** Use fire extinguishing methods suitable to surrounding conditions.

**Specific Hazards Arising from the Chemical:**

Hazardous combustion products include oxides of carbon and lithium.

This product is not flammable, but organic ingredients will burn in a fire.

If heated batteries may burst and release hazardous flammable or corrosive materials.

Batteries close to fire should be removed if safe to do so. Use water spray to cool fire exposed batteries.

**Special Protective Equipment and Precautions for Fire Fighters:**

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

### 6 Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:**

Wear approved respiratory protection, chemical goggles, neoprene or natural rubber gloves, protective clothing, impervious clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Do not touch or walk through spilled material.

**Environmental Precautions:**

In the event of a major spill, prevent spillage from entering drains or water courses.

**Methods and Materials for Containment and Cleaning Up:**

Absorb spilled liquid with sand, earth, vermiculite or some other absorbent material. Carefully collect batteries and place in an appropriate container for disposal. Provide adequate ventilation. Clean the area of spill with water and detergent.

### 7 Handling and Storage

**Precautions for Safe Handling:**

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours.

Avoid mechanical or electrical abuse.

DO NOT short circuit or install incorrectly.

Batteries may explode, pyrolyze or vent if disassembled, crushed, overcharged or exposed to high temperatures.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

**Conditions for Safe Storage:**

Store in a cool, dry and well ventilated area. Protect from direct sunlight, heat and open flames, water or seawater.

Keep away from oxidising agents, acids and bases. Do not store with other metal objects where they may be short circuited.

### 8 Exposure Controls and Personal Protection

**Exposure Standards:**

**CAS: 7782-42-5 Graphite**

WES TWA: 3 mg/m<sup>3</sup>

**CAS: 7440-50-8 Copper**

WES TWA: 1\* 0.2\*\* mg/m<sup>3</sup>  
\*dust & mists (as Cu) \*\*fume

(Contd. on page 4)

# Safety Data Sheet

## according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 3)

|                                 |   |
|---------------------------------|---|
| <b>CAS: 7429-90-5 Aluminium</b> |   |
| WES                             | TWA: 10* 5** mg/m <sup>3</sup><br>*metal dust;**welding, pyro powders |
| <b>CAS: 7440-02-0 Nickel</b>    |   |
| WES                             | TWA: 1 mg/m <sup>3</sup><br>Metal: Sen                                |

**Engineering Controls:** Natural ventilation should be adequate under normal use conditions.

**Respiratory Protection:** Respiratory protection is not required under normal use conditions.

**Skin Protection:**

Skin protection is not required under normal use conditions.

Use neoprene or natural rubber gloves, impervious clothing and safety boots is recommended if handling an open or leaking battery.

**Eye and Face Protection:**

Eye protection is not required under normal use conditions.

Wear safety glasses with sideshields or chemical goggles if handling an open or leaking battery.

## 9 Physical and Chemical Properties

**Appearance:**

|   |                           |
|---|---------------------------|
| <b>Form:</b>                                    | Solid                     |
| <b>Colour:</b>                                  | Black                     |
| <b>Odour:</b>                                   | No information available  |
| <b>Odour Threshold:</b>                         | No information available  |
| <b>pH-Value:</b>                                | No information available  |
| <b>Melting point/freezing point:</b>            | No information available  |
| <b>Initial Boiling Point/Boiling Range:</b>     | No information available  |
| <b>Flash Point:</b>                             | No information available  |
| <b>Flammability:</b>                            | Product is not flammable. |
| <b>Auto-ignition Temperature:</b>               | No information available  |
| <b>Decomposition Temperature:</b>               | No information available  |
| <b>Explosion Limits:</b>                        |                           |
| <b>Lower:</b>                                   | No information available  |
| <b>Upper:</b>                                   | No information available  |
| <b>Vapour Pressure:</b>                         | No information available  |
| <b>Relative Density:</b>                        | No information available  |
| <b>Vapour Density:</b>                          | No information available  |
| <b>Evaporation Rate:</b>                        | No information available  |
| <b>Solubility in Water:</b>                     | No information available  |
| <b>Partition Coefficient (n-octanol/water):</b> | No information available  |
| <b>Viscosity:</b>                               | No information available  |

## 10 Stability and Reactivity

**Possibility of Hazardous Reactions:** Hazardous polymerisation will not occur.

**Chemical Stability:** Stable at ambient temperature and under normal conditions of use.

**Conditions to Avoid:**

Direct sunlight, heat and open flames, water or sea-water.

Do not disassemble, crush or short circuit. Avoid mechanical or electrical abuse.

**Incompatible Materials:** Oxidising agents, acids and bases.

(Contd. on page 5)

# Safety Data Sheet

according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 4)

**Hazardous Decomposition Products:** Oxides of carbon and lithium.

## 11 Toxicological Information

**Toxicity:****LD50/LC50 Values Relevant for Classification:****CAS: 7440-50-8 Copper**

Oral LD50 &gt;2,000 mg/kg (rat)

**CAS: 7440-02-0 Nickel**

Oral LD50 &gt;9,000 mg/kg (rat)

**Acute Health Effects****Inhalation:** Contents of an open battery may cause respiratory irritation.**Skin:** Contents of an open battery may cause skin irritation. May cause an allergic skin reaction.**Eye:** Contents of an open battery may cause eye irritation.**Ingestion:** The contents of an open battery may cause gastrointestinal irritation.**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.**Serious Eye Damage / Irritation:** Based on classification principles, the classification criteria are not met.**Respiratory or Skin Sensitisation:**

Sensitisation possible through skin contact.

May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Suspected of causing cancer.

Nickel, metallic is classified by IARC as Group 2B - Possibly carcinogenic to humans.

**Reproductive Toxicity:** Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:**

Based on classification principles, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** No information available**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available

## 12 Ecological Information

**Ecotoxicity:****Aquatic toxicity:**

Toxic to aquatic life with long lasting effects.

**CAS: 7440-50-8 Copper**

EC50/48 h 0.792 mg/l (daphnia)

EC50/72 h 0.333 mg/l (algae)

LC50/96 h 0.0068-0.0156 mg/l (fathead minnow)

0.0081 mg/l (fish)

(Contd. on page 6)

# Safety Data Sheet

according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 5)

|                              |                  |
|------------------------------|------------------|
| <b>CAS: 7440-02-0 Nickel</b> |                  |
| EC50/48 h                    | 1 mg/l (daphnia) |
| LC50/96 h                    | 1.3 mg/l (carp)  |

**Persistence and Degradability:** No further relevant information available.**Bioaccumulative Potential:** No further relevant information available.**Mobility in Soil:** No further relevant information available.**Other adverse effects:** No further relevant information available.

## 13 Disposal Considerations

**Disposal Methods and Containers:** Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

## 14 Transport Information

|                              |  |
|------------------------------|--|
| <b>UN Number</b>             | UN3480   |
| <b>ADG, IMDG, IATA</b>       |  |
| <b>Proper Shipping Name</b>  | LITHIUM ION BATTERIES, ENVIRONMENTALLY HAZARDOUS   |
| <b>ADG</b>                   | LITHIUM ION BATTERIES (Copper), MARINE POLLUTANT   |
| <b>IMDG</b>                  | LITHIUM ION BATTERIES                              |
| <b>IATA</b>                  |  |
| <b>Dangerous Goods Class</b> |  |
| <b>ADG Class:</b>            | 9 Miscellaneous dangerous substances and articles. |
| <b>Packing Group:</b>        | Not applicable                                     |
| <b>Marine pollutant:</b>     | Yes  |
|                              | Symbol (fish and tree)                             |
| <b>EMS Number:</b>           | F-A,S-B  |
| <b>Hazchem Code:</b>         | 4W   |
| <b>Special Provisions:</b>   | 188, 230, 310, 348, 376, 377, 384, 387             |

SP188 states:

Cells and batteries offered for transport are not subject to other provisions of this Code if they meet the following:

(a) For a lithium metal or lithium alloy cell, the lithium content is not more than 1 g, and for a lithium-ion cell, the Watt-hour rating is not more than 20 Wh; and

(b) For a lithium metal or lithium alloy battery the aggregate lithium content is not more than 2 g, and for a lithium-ion battery, the Watt-hour rating is not more than 100 Wh. Lithium ion batteries subject to this provision must be marked with the Watthour rating on the outside case; and

(c) Each cell or battery is of the type proved to meet the requirements of each test in the Manual of Tests and Criteria, Part III, sub-section 38.3; and

(d) Cells and batteries, except when installed in equipment, must be packed in inner packagings that completely enclose the cell or battery. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with

(Contd. on page 7)

# Safety Data Sheet

## according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 6)

conductive materials within the same packaging that could lead to a short circuit. The inner packagings must be packed in strong outer packagings which conform to the provisions of 4.1.1.1, 4.1.1.2, and 4.1.1.5; and

(e) Cells and batteries when installed in equipment must be protected from damage and short circuit, and the equipment must be equipped with an effective means of preventing accidental activation. When lithium batteries are installed in equipment, the equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained; and

(f) Each package shall be marked with the appropriate lithium battery mark, as illustrated at 5.2.1.9;

NOTE 1: The provisions concerning marking in special provision 188 of the eighteenth revised edition of the United Nations Recommendations on the Transport of Dangerous Goods, Model Regulations may continue to be applied until 31 December 2018.

NOTE 2: Packages containing lithium batteries packed in conformity with the provisions of Part 4, Chapter 11, packing instructions 965 or 968, Section IB of the ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air that bear the mark as shown in 5.2.1.9 (lithium battery mark) and the label shown in 5.2.2.1.9, Model No.9A shall be deemed to meet the provisions of this special provision.

This requirement does not apply to:

(i) packages containing only button cell batteries installed in equipment (including circuit boards); and

(ii) packages containing no more than four cells or two batteries installed in equipment, where there are not more than two packages in the consignment. When packages are placed in an overpack, the lithium battery mark shall either be clearly visible or be reproduced on the outside of the overpack and the overpack shall be marked with the word "OVERPACK". The lettering of the "OVERPACK" mark shall be at least 12 mm high.

(g) Except when lithium batteries are installed in equipment, each package must be capable of withstanding a 1.2 m drop test in any orientation without damage to cells or batteries contained therein, without shifting of the contents so as to allow battery to battery (or cell to cell) contact and without release of contents; and

(h) Except when lithium batteries are installed in or packed with equipment, packages must not exceed 30 kg gross mass. As used above and elsewhere in this Code, "lithium content" means the mass of lithium in the anode of a lithium metal or lithium alloy cell. As used in this special provision "equipment" means apparatus for which the lithium cells or batteries will provide electrical power for its operation.

As used above and elsewhere in this Code, "lithium content" means the mass of lithium in the anode of a lithium metal or lithium alloy cell. As used in this special provision "equipment" means apparatus for which the lithium cells or batteries will provide electrical power for its operation.

Separate entries exist for lithium metal batteries and lithium ion

(Contd. on page 8)

# Safety Data Sheet

## according to WHS Regulations

Printing date 15.09.2020

Revision: 15.09.2020

**Product Name: POWER STATION**

(Contd. of page 7)

batteries to facilitate the transport of these batteries for specific modes of transport and to enable the application of different emergency response actions.

A single cell battery as defined in Part III, sub-section 38.3.2.3 of the Manual of Tests and Criteria is considered a "cell" and shall be transported according to the requirements for "cells" for the purpose of this special provision.

**Limited Quantities:** 0

**Packagings & IBCs - Packing Instruction:** P903, P908, P909, P910, LP903, LP904

### 15 Regulatory Information

#### Australian Inventory of Chemical Substances:

CAS: 7782-42-5 Graphite

CAS: 7440-50-8 Copper

CAS: 7440-02-0 Nickel

**Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:** Not Scheduled.

#### Australia: Priority Existing Chemicals

None of the ingredients is listed.

### 16 Other Information

**Date of Preparation or Last Revision:** 15.09.2020

**Prepared by:** MSDS.COM.AU Pty Ltd

[www.msds.com.au](http://www.msds.com.au)

#### Abbreviations and acronyms:

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Skin Sensitisation 1: Skin sensitisation, Hazard Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment, short-term (Acute). Category 1

Aquatic Acute 2: Hazardous to the aquatic environment, short-term (Acute). Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term (Chronic). Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

#### Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - May 2018"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Adventure Operations makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.